

CITS3007 Secure Coding

Secure software development

Unit coordinator: Arran Stewart


Highlights

- ▶ Threat modelling with STRIDE
- ▶ Testing basics

Four questions – activities

1. What are we building?
 - ▶ Outcome: a *model* or diagram of the system (and identified assets)
2. What can go wrong?
 - ▶ Outcome: prioritized list of threats
3. What are we going to do about it?
 - ▶ Outcome: prioritized list of mitigations or countermeasures
4. Did we do a good job?
 - ▶ Outcome: validation of prior steps; tests; gaps identified; improvements to process

Iterable



Scope

“Small and often” is better than “comprehensive, but never finished”.

- ▶ *Full* inventory of all potential threats for a large, complex system could be huge
- ▶ But it's better to do *something than nothing*, and it's better to identify the *most critical* threats than to aim for completeness

First pass = focus on biggest, most likely threats, to high-value assets

- ▶ Other assets and threats can be dealt with later; scope can be increased

Iterating a model

We can always note down spots where a model could be improved later.

Phrases to watch out for: “sometimes”, “also”.

- ▶ “*sometimes* this data store is used for *X*”, “this component is *also* used for *Y*” ⇒ more detail could be useful

Identify assets

These are things we want to protect.

Usually data.

But could also be:

- ▶ hardware
- ▶ information technology resources (like bandwidth, computational capacity)
- ▶ physical resources (electricity)

Can you think of threats targeting these?

Identify assets

Assets should be *prioritized* – which are most important?

- ▶ We could try to hide *everything* about our server, for example
 - ▶ But is the best use of our time?
- ▶ Compare server details with (e.g.) financial data, password hashes, cryptographic keys

Identify assets

Don't try and put a dollar value on assets. Avoid superfluous and unrealistic granularity.

- ▶ One idea: categorize with “T-shirt sizes”
- ▶ “Large” (major assets), “Medium” (valuable assets, but less critical), “Small” (minor consequence).
 - ▶ ... maybe your project needs “Extra-large” (super-critical)?

Remember other parties/stakeholders' viewpoints – something *you* think is of “minor consequence” could be much more important to (e.g.) a customer, CEO, finance, etc.

What can go wrong? – Identify threats

Methodically go through the model, component by component, flow by flow, looking for possible threats.

Identify

- ▶ *attack surfaces* (places an attack could originate)
 - ▶ Points where an attacker could interpose themselves
- ▶ *trust boundaries* (the borders between more-trusted and less-trusted parts of the system)
 - ▶ These will intersect data flows
- ▶ threats in each of the possible STRIDE categories.

Tip: threats often lurk at trust boundaries.

Identify attack surfaces

These are an attacker's "points of entry", or opportunities for attack. (For example: communication over a network.)

- ▶ When we look at mitigations – try to completely remove, or at least reduce, opportunities for attack

Identify threats

For each of the STRIDE categories – e.g. tampering – we ask, What advantages could an attacker gain if they did/subverted X?

A suggested approach: brainstorm first – come up with ideas quickly, without critiquing or judging them yet

Mitigations and other approaches

- ▶ *Mitigate* risk by redesigning or adding defenses.
 - ▶ The aim is either to reduce the chance of the risk occurring, or lower degree of harm to an acceptable level
- ▶ *Remove* a threatened asset if it is not actually needed
 - ▶ Or if removal is not possible – seek to reduce the exposure of the asset, or limit optional features of your system that increase the threat.

Mitigations and other approaches

- ▶ *Transfer* the risk – offload responsibility to a third party.
 - ▶ Example: Insurance is a common type of risk transfer
 - ▶ Example: Outsource responsibility for e.g. processing payments, or processing sensitive data, to an enterprise with expertise in the area.
- ▶ *Accept* the risk (once it's well understood) as being reasonable to incur.

Mitigations – questions to ask

- ▶ Can we make the attack less likely to work?
- ▶ Can we make the harm less severe – perhaps only some of the data is accessible?
- ▶ Can we make it possible to undo the harm – e.g. backups?
- ▶ Can we make it more obvious when harm has occurred – e.g. by ensuring we have comprehensive logging and monitoring?

Validation

- ▶ For a model – does it match what has actually been implemented?
- ▶ For threats – have we describe them properly? missed any?
 - ▶ do they: describe the attack, the context, the impact?
- ▶ Other stakeholders – have testing/quality assurance staff reviewed the model?
- ▶ Mitigations – is each threat mitigated (or otherwise dealt with)
- ▶ Are the mitigations done correctly? Have they been tested?

Testing functions

- ▶ How do we know what a function is supposed to do?
⇒ Refer to its documentation.
- ▶ Could be
 - ▶ a man page (e.g. for `strlen`)
 - ▶ extracted API documentation

Testing functions

strlen

NAME

strlen — calculate the length of a string

SYNOPSIS

```
#include <string.h>
```

```
size_t strlen(const char *s);
```

DESCRIPTION

The `strlen()` function calculates the length of the string pointed to by `s`, excluding the terminating null byte (`'\0'`).

- ▶ Are there any implicit requirements here?

API documentation systems

- ▶ An API comprises all functions, variables, and macros that are publicly available and documented as such
 - ▶ If a function says – “this is not part of the API” – you rely on it at your own risk
- ▶ Many languages come with API documentation generation tools
 - ▶ e.g. [Javadoc](#) for Java, [Pydoc](#) and Sphinx for Python, [Godoc](#) for Go
- ▶ C does not
 - ▶ Common tools used to extract C API information include [Doxygen](#) and [cldoc](#) (based on the Clang compiler)

Doxygen

Doxygen extracts API information from specially marked up comments – **documentation blocks**.

```
/** @brief Sets the position of the cursor to the
 *      position (row, col).
 *
 * Subsequent calls to putbytes should cause the console output to
 * begin at the new position. If the cursor is currently hidden, a call
 * to set_cursor() must not show the cursor.
 *
 * @param row The new row for the cursor.
 * @param col The new column for the cursor.
 */
void set_cursor(int row, int col);
```

Documentation blocks vs comments

- ▶ In C, API documentation is normally embedded in C comments
- ▶ But don't think of them as "comments" – they serve an entirely different purpose
- ▶ *Comments* are for maintainers and implementers of the code
 - ▶ Explain why and how something is implemented
 - ▶ Should be brief, and not clutter the code
- ▶ *Documentation* is for users of the code
 - ▶ Explains what the callers must do, and what they can expect
 - ▶ Can be as extensive as needed

API contents – bsearch

bsearch - binary search of a sorted array

```
#include <stdlib.h>

void *bsearch(const void *key, const void *base,
             size_t nmemb, size_t size,
             int (*compar)(const void *, const void *));
```

Description

The `bsearch()` function searches an array of `nmemb` objects, the initial member of which is pointed to by `base`, for a member that matches the object pointed to by `key`. The size of each member of the array is specified by `size`.

The contents of the array should be in ascending sorted order according to the comparison function referenced by `compar`. The `compar` routine is expected to have two arguments which point to the key object and to an array member, in that order, and should return an integer less than, equal to, or greater than zero if the key object is found, respectively, to be less than, to match, or be greater than the array member.

API contents – bsearch

bsearch - binary search of a sorted array

Return value

The `bsearch()` function returns a pointer to a matching member of the array, or `NULL` if no match is found. If there are multiple elements that match the key, the element returned is unspecified.

Tests in C

What do tests look like in C?

```
// test of strlen
const char * s = "somestring";
size_t expected_result = 10;
size_t actual_result = strlen(s);
if (expected_result != actual_result) {
    fprintf(stderr,
            "%s:%d: expected len to be %zd, but got %zd\n",
            __FILE__,
            __LINE__,
            expected_result,
            actual_result
    );
    exit(EXIT_FAILURE);
}
```


check

In labs, we will use the Check testing framework.

Install with:

```
sudo apt-get install check
```

There are many others, but Check has a number of advantages:

- ▶ Doesn't require any special build tools – gcc (and Make, if desired) are enough
- ▶ Protects the address space of the program under test using fork

Address space problems

In C, testing is more difficult, because the testing framework runs in the same address space as the function being tested.

If the function being tested corrupts memory, it could prevent the testing routines from working.

Check addresses this by `fork`-ing off a separate copy of the program for each test –

⇒ every test has its own address space.

Testing using check

- ▶ Easiest way: write tests in a test suite (".ts") file, and use the `checkmk` program to convert them into full `.c` code

mytests.ts

```
#suite adjust_score_tests

#tcase arithmetic_testcase

#test arithmetic_works
    int m = 3;
    int n = 4;
    int expected = 7;
    int actual = m + n;
    ck_assert_int_eq(actual, expected);
```

Compiling and running tests

We usually want to enable protective features and sanitizers

⇒ if a function fails, it fails as early and obviously as possible.

```
# compile
$ gcc -g -std=c11 -pedantic -Wall -Wextra -Wconversion \
  -fno-omit-frame-pointer \
  -fstack-protector-strong \
  -fsanitize=address,undefined,leak \
  -c -o myprog.o myprog.c
```

```
$ gcc -g -std=c11 -pedantic -Wall -Wextra -pthread \
  -fno-omit-frame-pointer \
  -fstack-protector-strong \
  -fsanitize=address,undefined,leak \
  -c -o mytests.o mytests.c
```


Mocks

When writing a test, we often want

- ▶ the test to run as fast as possible
- ▶ the test results to rely only on the function under test – not other extraneous systems

So what if we're testing a function that reads information from a file or database?

⇒ This is very slow, and adds a dependency on the filesystem or DBMS

⇒ If a test failure was reported, was it due to our function or the DB?

